

K-WTEH 2-TLG PC-BEHÄLTER S W H G-MINI

Service units, 2-piece with polycarbonate bowl and joiner for wall mounting, semi-automatic drain valve

HANSA FLEX

Karakteristike

| | |
|------------------------------------|--|
| Ulazni tlak | Max. 10 bar |
| Temperatura medija | max. 70 °C |
| Okolna temperatura | Max. 70 °C |
| Veličina pora u filternom elementu | 5 µm |
| Brtveni materijal | NBR |
| Pokrov s oprugom | POM |
| Kućište | Die-cast aluminium |
| Nastavak za kapanje | Brass/POM |
| Drain valve | Semi-automatic |
| Mjerenje vrijednosti protoka | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Drugi podatci | User manual on request |



Artikli

| Naziv | Navoj | Regulacijsko područje | Protok (L/min) | A (mm) | B | C (mm) | D (mm) | Veličina |
|----------------|-------|-----------------------|----------------|--------|----------|--------|--------|----------|
| K- 07 25 14 09 | G 1/8 | 1.5 - 9 bar | 500 | 88,0 | 161,0 mm | 68,0 | 93,0 | 200 |
| K- 07 25 14 10 | G 1/4 | 1.5 - 9 bar | 500 | 88,0 | 161,0 mm | 68,0 | 93,0 | 200 |

Pribor

| | |
|------------------------|-----------------------|
| K-VERSCHLEI-SATZ | Set of wearing parts |
| K-ERSATZMEMBRANE | Replacement diaphragm |
| K-ADAPTERPLATTEN HANSA | Adapter plate HANSA |
| K-FILTERELEMENT | Filter element |
| K-VERBINDUNGSELEMENTE | Connecting sets |
| K-WANDHALTER | Wall bracket |