# K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring

## Karakteristike

| | |
|---|---|
| **Mediji** | Air, neutral gases (filtered) |
| **Radni tlak** | 1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22) |
| **Radna temperatura** | -20 °C to +50 °C |
| **vodoravno Priključak 1 - 3** | G 1/4 (Port 1), G 1/4 (Port 3 and 5) |
| **Priključak 1/3 + 5** | G 1/4 (Port 1), G 1/4 (Port 3 and 5) |
| **Električni priključak** | Plug connector PG 9 |
| **Sadržano u opsegu isporuke** | Plug connector PG 9, conversion plate, screws and seal |
| **Potrošnja struje** | 3 W=/5 VA~ |
| **Kućište** | Anodised aluminium |
| **Klizač** | Stainless steel |
| **Brtveni materijal** | NBR |



## Napomena

Drugi podatci na zahtjev.

## Opis

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.
Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

## Artikl

| Naziv | Napon | Port 1 | Priključak 3 + 5 | DN | Protok (L/min) |
|---|---|---|---|---|---|
| **K- 07 15 00 13** | 230 V, 50 Hz | G 1/4 | G 1/4 | 7 | 1250 |
| **K- 07 15 00 14** | 24 V DC | G 1/4 | G 1/4 | 7 | 1250 |