K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring

Karakteristike

Mediji	Air, neutral gases (filtered)
Radni tlak	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
Radna temperatura	-20 °C to +50 °C
vodoravno Priključak 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Priključak 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Električni priključak	Plug connector PG 9
Sadržano u opsegu isporuke	Plug connector PG 9, conversion plate, screws and seal
Potrošnja struje	3 W=/5 VA~
Kućište	Anodised aluminium
Klizač	Stainless steel
Brtveni materijal	NBR



Napomena

Drugi podatci na zahtjev.

Opis

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.
Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Artikl

Naziv	Napon	Port 1	Priključak 3 + 5	DN	Protok (L/min)
K- 07 15 00 13	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 14	24 V DC	G 1/4	G 1/4	7	1250

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.