


K-VSTO POM

Plugs

HANSA FLEX

Karakteristike

| | |
|-------------------|---|
| Radni tlak | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm) |
| Radna temperatura | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| Materijal | Acetalpolymerisat (POM) |
| Brtveni materijal | NBR |



Napomena

Drugi podatci na zahtjev.

Opis

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Artikli

| Naziv | Boja | L1 (mm) | Nastavak (mm) |
|----------------|--------|------------|------------------|
| K- 07 40 29 11 | crvena | 28,0 | 4 |
| K- 07 40 29 12 | crvena | 28,0 | 5 |
| K- 07 40 29 13 | crvena | 30,0 | 6 |
| K- 07 40 29 14 | crvena | 31,0 | 8 |
| K- 07 40 29 15 | crvena | 36,5 | 10 |
| K- 07 40 29 16 | crvena | 38,5 | 12 |
| K- 07 40 29 17 | crna | 45,0 | 15 |
| K- 07 40 29 18 | crna | 41,5 | 18 |
| K- 07 40 29 19 | crna | 45,0 | 22 |
| K- 07 40 29 20 | crna | 56,0 | 28 |