

# K-FI PC-BEHÄLTER HW G-MINI

Filters

**HANSA FLEX**

## Karakteristike

|                                      |  |
|--------------------------------------|--|
| Ulazni tlak                          | Max. 10 bar  |
| Temperatura medija                   | max. 70 °C   |
| Okolna temperatura                   | Max. 70 °C   |
| Radni tlak                           | 1.5 - 9 bar  |
| Veličina pora u filteraskom elementu | 5 µm   |
| Brtnveni materijal                   | NBR  |
| Kućište                              | Die-cast aluminium   |
| Drain valve                          | Semi-automatic   |
| Mjerenje vrijednosti protoka         | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Drugi podatci                        | User manual on request   |



## Artikl

| Naziv          | Navoj | Protok (L/min) | A (mm) | B        | C (mm) | D (mm) | Veličina |
|----------------|-------|----------------|--------|----------|--------|--------|----------|
| K- 07 25 06 49 | G 1/8 | 950            | 38,0   | 110,0 mm | 17,0   | 93,0   | 200      |
| K- 07 25 06 50 | G 1/4 | 950            | 38,0   | 110,0 mm | 17,0   | 93,0   | 200      |

## Pribor

|                                    |   |
|------------------------------------|---|
| K-ERSATZBEHÄLTER G UND G-MINI POLY | Spare tanks »G« Series and »G-mini« Series Polycarbonat |
| K-SCHUTZKORB G                     | Protective cage   |
| K-FILTERELEMENT                    | Filter element  |
| K-HALTERBAUSATZ                    | Holder  |
| K-VERBINDUNGSELEMENTE              | Connecting sets   |
| K-WANDHALTER                       | Wall bracket  |