

K-MV G (NC) D 24 V DC H 1

Normally closed, (NC), directly operated, 24 V DC, for high pressures

HANSA FLEX

Karakteristike

Električni priključak	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
Vrsta zaštite	IP 65
Temperatura medija	max. 80 °C when using water or oils; max. 90 °C when using with air
Opis navoja	G thread acc. DIN EN ISO 228-1
Kućište, dosjed ventila	Brass
Unutarnji dijelovi	Stainless steel
Brtva	FPM



Napomena

Drugi podatci na zahtjev.

Opis

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Artikli

Naziv	Navoj	maks. radni tlak (bar)	Nazivni promjer	A (mm)	B (mm)	C (mm)	Oblik izrade
K- 07 30 01 68	G 1/8	30	1,5	70,0	40,0	70,7	1
K- 07 30 01 69	G 1/4	30	1,5	70,0	40,0	70,7	1
K- 07 30 01 70	G 3/8	30	3,0	85,0	52,0	87,0	1
K- 07 30 01 71	G 1/2	30	3,0	85,0	52,0	87,0	1