


K-L-STECKVER DREH MINI

Male elbows, swivel type, mini

HANSA FLEX

Karakteristike

Radni tlak	Max. 10 bar, vacuum
Područje primjene	Air, vacuum
preporučena crijeva	PU or PA (nylon)
Mediji	komprimirani zrak
Norma	M thread acc. to DIN 13-1, with O-Ring G thread acc. to DIN EN ISO 228-1, with O-Ring R thread acc. to ISO 7-1, thread coating
Temperaturno područje	0 °C to +60 °C
Brtvena površina	O-ring (NBR)
Materijal	Plastic, Nickel plated brass
Pritisni prsten	Plastic



Napomena

Drugi podatci na zahtjev.

Opis

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

Artikli

Naziv	Navoj	za vanjski Ø crijeva	L1 (mm)	L2 (mm)	SW (veličina ključa)
K- 07 40 23 43	M 3	3 mm	12,0	16,0	8 mm
K- 07 40 23 44	M 3	4 mm	14,0	17,2	8 mm
K- 07 40 23 45	M 5	3 mm	12,0	16,0	8 mm
K- 07 40 23 46	M 5	4 mm	14,0	17,2	8 mm
K- 07 40 23 47	M 5	6 mm	16,0	17,2	8 mm
K- 07 40 23 48	M 6	3 mm	12,0	16,5	10 mm
K- 07 40 23 49	M 6	4 mm	14,0	17,6	10 mm
K- 07 40 23 50	M 6	6 mm	16,0	17,6	10 mm
K- 07 40 23 51	G 1/8	4 mm	14,0	16,5	13 mm
K- 07 40 23 52	G 1/8	6 mm	16,0	16,5	13 mm
K- 07 40 23 65	R 1/8	4 mm	14,0	18,0	10 mm
K- 07 40 23 66	R 1/8	6 mm	16,0	18,0	10 mm
K- 07 40 50 05	M 7	4 mm	14,0	15,7	10 mm
K- 07 40 50 06	M 7	6 mm	16,3	17,2	10 mm