

# K-SCHALLDAE SINTERBR GE MS

Silencers, sintered bronze, with brass hexagon nut and brass thread

**HANSA FLEX**

## Karakteristike

|                   |                   |
|-------------------|-------------------|
| Radni tlak        | maks. 10 bar      |
| Radna temperatura | -10 °C to +200 °C |
| Razina buke 6 bar | 80 ~ 90 dB(A)     |



## Opis

For reducing the exhaust noise generated by pneumatic equipment.

## Artikl

| Naziv          | Navoj | A<br>(mm) | B<br>(mm) | C<br>(mm) | SW (veličina ključa) |
|----------------|-------|-----------|-----------|-----------|----------------------|
| K- 07 40 35 11 | M 5   | 5,0       | 20,8      | 4,0       | 9 mm                 |
| K- 07 40 35 12 | G 1/8 | 5,5       | 22,8      | 8,0       | 13 mm                |
| K- 07 40 35 13 | G 1/4 | 7,0       | 33,5      | 10,0      | 17 mm                |
| K- 07 40 35 14 | G 3/8 | 9,0       | 41,7      | 14,0      | 22 mm                |
| K- 07 40 35 15 | G 1/2 | 10,0      | 48,5      | 18,0      | 24 mm                |