

# K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

**HANSA FLEX**

## Karakteristike

Radni tlak	maks. 10 bar
Protok zraka	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatura medija	-20 °C to +150 °C
Kućište	Stainless steel 1.4404
Navoj	Stainless steel 1.4404
Unutarnji dijelovi	Stainless steel 1.4404
Gumb, ventil	Stainless steel 1.4404
Brtveni materijal	FKM



## Napomena

Not suitable for hitting / pulsating tools.

Drugi podatci na zahtjev.

## Opis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## Dodatne informacije

Not suitable for hitting / pulsating tools.

## Artikl

Naziv	Priključak	Duljina (mm)	SW (mm)
K- 07 35 12 79	G 1/4 female	71,5	21
K- 07 35 12 80	G 3/8 female	75,5	21
K- 07 35 12 81	G 1/2 female	77,5	24