

# K-DV GEW B RAENDEL

Bidirectional flow control valves, air restriction at both ends («B»), screw connection

**HANSA FLEX**

## Karakteristike

|   |                                    |
|---|------------------------------------|
| Radni tlak  | maks. 10 bar                       |
| Temperaturno područje                             | 0 °C to +70 °C                     |
| Šuplji vijak, zakretni krak, vijak za reguliranje | Nickel-plated brass                |
| Unutarnji dijelovi                                | Brass with a bare metal surface    |
| Brtvena usna O-prsten                             | NBR                                |
| Brtve (sa zaštitom od ispadanja)                  | Polyamide (glass fibre-reinforced) |



## Napomena

Drugi podatci na zahtjev.

## Opis

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. <br>On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

## Artikli

| Naziv          | Priključak          | C (mm) | Navoj | SW (veličina ključa) | B (mm) |
|----------------|---------------------|--------|-------|----------------------|--------|
| K- 07 15 25 16 | M 5 female thread   | 11,5   | M 5   | 8 mm                 | 38,9   |
| K- 07 15 04 97 | G 1/8 female thread | 16,0   | G 1/8 | 14 mm                | 42,0   |
| K- 07 15 04 93 | G 1/4 female thread | 22,0   | G 1/4 | 17 mm                | 51,0   |
| K- 07 15 25 17 | G 1/2 female thread | 32,0   | G 1/2 | 26 mm                | 81,0   |
| K- 07 15 25 18 | G 3/8 female thread | 26,0   | G 3/8 | 20 mm                | 63,0   |