

K-L-STECKVER DREH AG-K VA

Male elbows, swivel type, conical male thread

HANSA FLEX

Karakteristike

| | |
|-------------------------------|---|
| Radni tlak, pulsirajući | Max. 10 bar |
| Tlak | Max. 15 bar (depending on pipe quality) |
| prikladan materijal za cijevi | PVDF, PTFE, stainless steel, PA, PU |
| Norma | R thread acc. to ISO 7-1 |
| Okolna temperatura | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Materijal | Oplemenjeni čelik 1.4404 |
| Brtnveni materijal | FKM |



Napomena

Drugi podatci na zahtjev.

Opis

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Artikli

| Naziv | Navoj | za vanjski Ø crijeva | L1 (mm) | L2 (mm) | SW (veličina ključa) |
|----------------|-------|----------------------|------------|------------|----------------------|
| K- 07 40 24 44 | R 1/8 | 4 mm | 17,0 | 17,5 | 10 mm |
| K- 07 40 24 45 | R 1/8 | 6 mm | 21,5 | 20,0 | 13 mm |
| K- 07 40 24 46 | R 1/8 | 8 mm | 22,0 | 20,0 | 13 mm |
| K- 07 40 24 42 | R 1/4 | 6 mm | 21,5 | 24,0 | 14 mm |
| K- 07 40 24 43 | R 1/4 | 8 mm | 22,0 | 24,0 | 14 mm |
| K- 07 40 24 41 | R 1/4 | 10 mm | 25,5 | 26,5 | 16 mm |
| K- 07 40 24 47 | R 3/8 | 10 mm | 25,5 | 27,0 | 17 mm |
| K- 07 40 24 48 | R 3/8 | 12 mm | 28,0 | 30,5 | 22 mm |
| K- 07 40 24 40 | R 1/2 | 12 mm | 28,0 | 33,5 | 22 mm |