

# K-L-STECKVER AG-K VA

Male elbows conical male thread

**HANSA FLEX**

## Karakteristike

Radni tlak, pulsirajući	Max. 10 bar
Tlak	Max. 15 bar (depending on pipe quality)
prikladan materijal za cijevi	PVDF, PTFE, stainless steel, PA, PU
Norma	R thread acc. to ISO 7-1
Okolna temperatura	-20 °C to max. +150 °C (depending on pipe quality and diameter)
Materijal	Oplemenjeni čelik 1.4404
Brtnveni materijal	FKM



## Napomena

Drugi podatci na zahtjev.

## Opis

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Artikli

Naziv	Navoj	za vanjski Ø crijeva	L1 (mm)	L2 (mm)
K- 07 40 24 37	R 1/8	4 mm	17,0	16,0
K- 07 40 24 38	R 1/8	6 mm	20,0	16,0
K- 07 40 24 39	R 1/8	8 mm	21,0	17,0
K- 07 40 24 35	R 1/4	6 mm	20,0	20,0
K- 07 40 24 36	R 1/4	8 mm	21,0	20,0
K- 07 40 46 80	R 1/4	10 mm	25,5	22,5