

# K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick disconnect couplings and stems DN 7.2

**HANSA FLEX**

## Karakteristike

Unutrašnji sloj Soft-PVC, black

Umetak Pletivo od poliestera

Vanjski sloj Soft-PVC, blue

Radna temperatura -20 °C to +60 °C



## Napomena

Drugi podatci na zahtjev.

## Opis

Highly flexible hose for compressed air applications in workshop areas. Assembled with brass stem and brass quick disconnect coupling DN 7.2

## Artikli

Naziv	Ø crijeva iznutra (mm)	Ø crijeva izvana (mm)	maks. radni tlak pri 20°C (bar)	Duljina crijeva (m)
K- 07 10 11 91	6,3	11,0	15	5
K- 07 10 11 85	6,3	11,0	15	10
K- 07 10 11 87	6,3	11,0	15	15
K- 07 10 11 88	6,3	11,0	15	20
K- 07 10 11 90	6,3	11,0	15	25
K- 07 10 11 99	9,0	14,5	15	5
K- 07 10 11 93	9,0	14,5	15	10
K- 07 10 11 95	9,0	14,5	15	15
K- 07 10 11 96	9,0	14,5	15	20
K- 07 10 11 98	9,0	14,5	15	25