


K-STECKVERSCHR RU AGR-K

Male connectors, round, conical male thread, coated with inner hex

HANSA FLEX

Karakteristike

Radni tlak	Max. 15 bar, coarse vacuum
Područje primjene	Air, vacuum
preporučena crijeva	PU or PA (nylon)
Mediji	Compressed air and all gases or liquids that are compatible with the materials
Temperaturno područje	-20 °C to +80 °C
Brtvena površina	Conical version: thread coating
Materijal	Plastic, Nickel plated brass
Pritisni prsten	Plastic



Napomena

Drugi podatci na zahtjev.

Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artikli

Naziv	Navoj	za vanjski Ø crijeva	Imbus (mm)	L1 (mm)
K- 07 40 09 38	R 1/8	4 mm	3,0	19,8
K- 07 40 09 39	R 1/8	6 mm	4,0	20,7
K- 07 40 09 40	R 1/8	8 mm	5,0	27,1
K- 07 40 09 37	R 1/8	10 mm	5,0	29,6
K- 07 40 09 34	R 1/4	4 mm	3,0	17,9
K- 07 40 09 35	R 1/4	6 mm	4,0	22,5
K- 07 40 09 36	R 1/4	8 mm	5,0	24,6
K- 07 40 09 33	R 1/4	10 mm	6,0	30,9
K- 07 40 09 44	R 3/8	6 mm	4,0	20,1
K- 07 40 09 45	R 3/8	8 mm	6,0	24,6
K- 07 40 09 41	R 3/8	10 mm	8,0	26,9
K- 07 40 09 42	R 3/8	12 mm	8,0	29,6
K- 07 40 09 43	R 3/8	16 mm	8,0	38,1
K- 07 40 09 31	R 1/2	6 mm	4,0	24,1
K- 07 40 09 32	R 1/2	8 mm	6,0	25,6
K- 07 40 09 28	R 1/2	10 mm	8,0	25,3
K- 07 40 09 29	R 1/2	12 mm	8,0	32,6
K- 07 40 09 30	R 1/2	16 mm	10,0	35,1