

K-V90-RBO 98

Union elbow 98, taper seat, female/male

HANSA FLEX

Karakteristike

Površina	Hot dip galvanised
Temperaturno področje	-20 °C to +300 °C (at 20 bar)
Navoj priključka	acc. ISO 7-1
Materijal	Black malleable iron B350-10, design symbol A
Odobrenje	DIN DVGW



Napomena

Drugi podatki na zahtjev.

Opis

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

Dodatne informacije

Further types and dimensions on request.

Artiki

Naziv	Navoj 1	Navoj 2
K- 07 40 52 64	Rp 1/4	R 1/4
K- 07 40 52 63	Rp 1/2	R 1/2
K- 07 40 52 67	Rp 3/4	R 3/4
K- 07 40 52 60	Rp 1	R 1
K- 07 40 52 62	Rp 1 1/4	R 1 1/4
K- 07 40 52 61	Rp 1 1/2	R 1 1/2
K- 07 40 52 65	Rp 2	R 2
K- 07 40 52 66	Rp 2 1/2	R 2 1/2