

# K-STECKVERBINDU 2

Straight push-in connector

**HANSA FLEX**

## Karakteristike

|                   |                     |
|-------------------|---------------------|
| Radni tlak        | Max. 16 bar         |
| Radna temperatura | -20 °C to +150 °C   |
| Materijal         | poniklani mjed      |
| Pritisni prsten   | Nickel-plated brass |
| Stezni prsten     | Stainless steel     |



## Napomena

Drugi podatci na zahtjev.

## Opis

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Artikli

| Naziv          | za vanjski Ø crijeva | L1<br>(mm) |
|----------------|----------------------|------------|
| K- 07 40 27 49 | 4 mm                 | 31,0       |
| K- 07 40 27 50 | 6 mm                 | 33,0       |
| K- 07 40 27 51 | 8 mm                 | 37,0       |
| K- 07 40 27 52 | 10 mm                | 39,0       |
| K- 07 40 47 74 | 12 mm                | 43,0       |
| K- 07 40 40 91 | 14 mm                | 47,5       |