

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Karakteristike

Unutrašnji sloj Soft-PVC, black

Umetak Pletivo od poliestera

Vanjski sloj Soft-PVC, blue

Temperatura -20 °C to +60 °C

Duljina valjaka 50 m



Napomena

Drugi podatci na zahtjev.

Opis

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Artikl

Naziv	Ø crijeva iznutra (mm)	Ø crijeva izvana (mm)	Max. working pressure resistance at 23°C (bar)	Radius savijanja min. (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88