

K-SCHOTT-STECKVERB RED

Female bulkhead connectors, unequal

HANSA FLEX

Karakteristike

| | |
|-------------------|------------------|
| Radni tlak | Max. 16 bar |
| Radna temperatura | -20 °C to +80 °C |
| Materijal | poniklani mjed |
| Pritisni prsten | Hostaform |
| Stezni prsten | Stainless steel |



Napomena

Drugi podatci na zahtjev.

Opis

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Artikl

| Naziv | Navoj | za vanjski Ø crijeva | L1 (mm) | SW (veličina ključa) |
|----------------|----------|----------------------|------------|----------------------|
| K- 07 40 25 51 | M 13 x 1 | 4 mm / 6 mm | 32,7 | 16 mm |
| K- 07 40 25 54 | M 15 x 1 | 4 mm / 8 mm | 34,4 | 17 mm |
| K- 07 40 25 55 | M 15 x 1 | 6 mm / 8 mm | 35,0 | 17 mm |
| K- 07 40 25 57 | M 17 x 1 | 6 mm / 10 mm | 37,5 | 20 mm |
| K- 07 40 25 58 | M 17 x 1 | 8 mm / 10 mm | 37,8 | 20 mm |
| K- 07 40 47 17 | M 20 x 1 | 10 mm / 12 mm | 40,8 | 24 mm |
| K- 07 40 47 18 | M 20 x 1 | 6 mm / 12 mm | 39,0 | 24 mm |
| K- 07 40 47 19 | M 20 x 1 | 8 mm / 12 mm | 40,1 | 24 mm |