

# K-DLV MULTI-LINK OHNE KUPPLU

Compressed air distributor, type »Multi-Link« without couplings, female thread

**HANSA FLEX**

## Karakteristike

<b>Radni tlak</b>	Max. 16 bar
<b>Temperaturno področje</b>	od -20 °C do +100 °C (-20 °C to +80 °C quickconnect-safety couplings)
<b>Materijal</b>	Galvanised steel / brass
<b>Priključak</b>	G 1/2 female
<b>Mediji</b>	Compressed air, non-corrosive gases
<b>Brtveni material</b>	NBR



## Napomena

Drugi podatki na zahtjev.

## Opis

Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 1 to 5 bleed units, optionally with:

- G 1/2 female threaded connection for individually adaption output segments,
- DN 7.6 standard quick disconnect couplings,
- DN 7.6 quick disconnectsafety couplings.

## Artiki

Naziv	Priključak	Jedinice za vađenje
K- 07 35 13 68	G 1/2 female	1
K- 07 35 13 71	G 1/2 female	2
K- 07 35 13 74	G 1/2 female	3
K- 07 35 13 77	G 1/2 female	4
K- 07 35 13 80	G 1/2 female	5