

# K-T-STECK VERS DRE AG OR VA

Male branch tees, swivel type, parallel male thread with O-ring

**HANSA FLEX**

## Karakteristike

|                               |   |
|-------------------------------|---|
| Radni tlak, pulsirajući       | Max. 10 bar   |
| Tlak                          | Max. 15 bar (depending on pipe quality)                         |
| prikladan materijal za cijevi | PVDF, PTFE, stainless steel, PA, PU                             |
| Norma                         | G thread acc. to DIN EN ISO 228-1, with O-Ring                  |
| Okolna temperatura            | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Materijal                     | Oplemenjeni čelik 1.4404  |
| Brtnveni materijal            | FKM   |



## Napomena

Drugi podatci na zahtjev.

## Opis

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Artikli

| Naziv          | Navoj | za vanjski Ø crijeva | L1<br>(mm) | L2<br>(mm) | SW (veličina ključa) |
|----------------|-------|----------------------|------------|------------|----------------------|
| K- 07 40 46 81 | M 5   | 4 mm                 | 34,0       | 18,0       | 9 mm                 |
| K- 07 40 24 52 | G 1/8 | 4 mm                 | 34,0       | 20,0       | 13 mm                |
| K- 07 40 24 53 | G 1/8 | 6 mm                 | 42,0       | 22,5       | 13 mm                |
| K- 07 40 24 54 | G 1/8 | 8 mm                 | 43,0       | 22,5       | 13 mm                |
| K- 07 40 24 50 | G 1/4 | 6 mm                 | 42,0       | 24,5       | 16 mm                |
| K- 07 40 24 51 | G 1/4 | 8 mm                 | 43,0       | 24,5       | 16 mm                |
| K- 07 40 24 49 | G 1/4 | 10 mm                | 50,0       | 25,5       | 16 mm                |
| K- 07 40 24 55 | G 3/8 | 10 mm                | 50,0       | 27,0       | 21 mm                |