K-LECKAGESUCHGERAET
Leakage finder

Karakteristike

Radna frekvencija	40 kHz ± 2 kHz
Priključak	4-pin connection for headphones and charger, 3.5 mm stereo jack for connecting sensor and cable
Laser	Wave length: 655 to 660 nm, Output power: 0.4 to 0.5 mW
Opskrba energijom	Internal NiMH rechargeable battery
Trajanje rada	Approx. 6 hours without laser / 4 hours with laser
Vrijeme punjenja	Approx. 1.5 hours
Temperatura primjene	0 °C to +40 °C
Temperatura skladištenja	-10 °C to +50 °C



Napomena
Drugi podatci na zahtjev.

Opis
Function: The annual energy cost of leaks in pneumatic and gas systems are high and avoidable. When these gases flow unused out of leaks, they create noises inaudible to the human ear. With the LS 100, even the smallest leaks can be heard from several metres distance. It transforms inaudible signals to a frequency that can be detected visually on the display and acoustically with the supplied sound-proof headphones. Use: leakage inspections of pneumatic, gas, steam and vacuum systems.
The advantages of the LS 100: Simple and quick measurement, even from distances of several metres Measurements can be taken on running systems, without affecting their operation
The device is quickly amortised by the high cost savings

Artikl

Naziv	Opis
K- 07 25 19 53	Leak detection device, including accessories in a practical carrying case

Pribor

K-ALU-TELESKOPSTANGE	Aluminium-telescopic pole

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.