

K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

HANSA FLEX

Karakteristike

Vrsta priključka	with pushbutton safety coupling NW 7,4 steel nipple galvanised
Radna temperatura	-40 °C to +74 °C



Napomena

Drugi podatci na zahtjev.

Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Nije prikladno za udarajuće ili pulsirajuće alate!

Artikl

Naziv	Ø crijeva iznutra (mm)	Ø crijeva izvana (mm)	Ø vanjskog namota (mm)	Max. working pressure resistance at 23°C (bar)	maks. radna duljina (m)
K-07 10 12 71	5,0	8,0	40	10	3,0
K-07 10 12 73	5,0	8,0	40	10	6,0
K-07 10 12 75	5,0	8,0	40	10	7,5
K-07 10 12 80	6,3	9,5	60	10	3,0
K-07 10 12 82	6,3	9,5	60	10	6,0
K-07 10 12 84	6,3	9,5	60	10	7,5
K-07 10 12 78	6,3	9,5	60	10	10,0
K-07 10 12 89	8,0	12,0	80	9	3,0
K-07 10 12 91	8,0	12,0	80	9	6,0
K-07 10 12 93	8,0	12,0	80	9	7,5
K-07 10 12 87	8,0	12,0	80	9	10,0

Pribor

K-DREHBARE VERSCHRAUBUNG Swivel adapters