


Karakteristike

| | |
|----------------------|---|
| Izvedba | Strugač |
| Brzina klizanja max. | 4,0 m/s |
| Temperatura min. | -40 °C |
| Temperatura max. | 110 °C |
| Mediji | mineralno ulje |
| Montaža | Strugač oblikovati u obliku bubrega i utisnuti u prihvatni utor |
| Primjena | For the usage at higher pollution, for e.g.: Mining foundries |
| Materijal | PU 93° Shore A |



Artikli

| Naziv | C (mm) | D (mm) | d (mm) | G (mm) | H (mm) | L (mm) |
|---------|-----------|-----------|-----------|-----------|-----------|-----------|
| WUH-26 | 32,0 | 34,0 | 26 | 5,00 | 8,7 | 4,0 |
| WUH-30 | 36,0 | 38,0 | 30 | 5,00 | 8,7 | 4,0 |
| WUH-32 | 38,0 | 40,0 | 32 | 5,00 | 8,7 | 4,0 |
| WUH-36 | 42,0 | 44,0 | 36 | 5,00 | 8,7 | 4,0 |
| WUH-40 | 46,0 | 48,0 | 40 | 5,00 | 8,7 | 4,0 |
| WUH-45 | 51,0 | 53,0 | 45 | 5,00 | 8,7 | 4,0 |
| WUH-50 | 56,0 | 58,0 | 50 | 5,00 | 8,7 | 4,0 |
| WUH-52 | 58,0 | 60,0 | 52 | 5,00 | 8,7 | 4,0 |
| WUH-56 | 62,0 | 64,0 | 56 | 5,00 | 8,7 | 4,0 |
| WUH-60 | 66,0 | 68,0 | 60 | 5,00 | 8,7 | 4,0 |
| WUH-68 | 74,0 | 76,0 | 68 | 5,00 | 8,7 | 4,0 |
| WUH-70 | 76,0 | 78,0 | 70 | 5,00 | 8,7 | 4,0 |
| WUH-75 | 81,0 | 83,0 | 75 | 5,00 | 8,7 | 4,0 |
| WUH-80 | 86,0 | 88,0 | 80 | 5,00 | 8,7 | 4,0 |
| WUH-100 | 107,0 | 110,0 | 100 | 8,10 | 11,7 | 6,3 |