

# K-3WSV ELKT OS HANSA PRO

3/2-way poppet valve electrically actuated, HANSA PRO

**HANSA FLEX**

## Karakteristike

|                      |  |
|----------------------|--|
| Temperatura medija   | -10 °C to +50 °C                             |
| Okolna temperatura   | -10 °C to +50 °C                             |
| Mediji               | komprimirani zrak                            |
| Vrsta zaštite        | IP 65 acc. to DIN 40050                      |
| Vrsta pričvršćenja   | Line mounting, mounting kit or wall mounting |
| Aktiviranje          | electrical                                   |
| Područje tlaka       | 2 - 10 bar                                   |
| Ugradbeni položaj    | Any  |
| Nazivni protok G 1/2 | 5.200 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| Nazivni protok G 3/8 | 4.300 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| PE maks. 11          | 10 bar                                       |
| Kućište              | PA66   |



## Artikl

| Naziv          | Priključak | Nazivni napon/ vrsta struje | Veličina |
|----------------|------------|-----------------------------|----------|
| K- 07 25 22 56 | G 3/8 i    | no coil                     | 2        |
| K- 07 25 22 57 | G 1/2 i    | no coil                     | 2        |