

K-VERTEILER 3-FACH HANSA PRO

Distributor 3-fold with pressure switch, HANSA PRO

HANSA FLEX

Karakteristike

| | |
|---------------------------------|--|
| Temperatura medija | -10 °C to +50 °C |
| Okolna temperatura | -10 °C to +50 °C |
| Mediji | komprimirani zrak |
| Vrsta pričvršćenja | Line mounting, mounting kit or wall mounting |
| Ugradbeni položaj | Any |
| Područje namještanja | 0,3 - 2 bar |
| Nazivni protok G 1/2 | 11.000 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Nazivni protok G 3/8 | 7.250 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Nazivni protok straga (P - E) | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Nazivni protok gore (P - D) | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Nazivni protok dolje (P - B) | 5.500 l/min (P1 = 6 bar/Delta P = 1 bar) |
| Nazivni protok sprijeda (P - C) | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar) |
| PE maks. 11 | 16 bar |
| Kućičšte | PA66 |



Artikli

| Naziv | Priključak P + A | Priključak B | Priključak C | Priključak D | Priključak E | Tlak pucanja (bar) | Veličina |
|----------------|------------------|--------------|--------------|--------------|--------------|--------------------|----------|
| K- 07 25 22 38 | G 3/8 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 5 | 2 |
| K- 07 25 22 39 | G 3/8 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 10 | 2 |
| K- 07 25 22 40 | G 3/8 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 20 | 2 |
| K- 07 25 22 41 | G 3/8 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 25 | 2 |
| K- 07 25 22 42 | G 1/2 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 5 | 2 |
| K- 07 25 22 43 | G 1/2 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 10 | 2 |
| K- 07 25 22 44 | G 1/2 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 20 | 2 |
| K- 07 25 22 45 | G 1/2 i | G 1/2 i | G 3/8 i | G 1/4 i | G 3/8 i | 25 | 2 |