

# K-W STECK VB 2-FACH WAND 20-63 INF1

2-fold angle connector Ø 20 mm - Ø 63 mm with wall mounting  
(adjustable)

**HANSA FLEX**

## Karakteristike

|                       |                                     |
|-----------------------|-------------------------------------|
| Mediji                | Compressed air, vacuum, inert gases |
| Radni tlak            | -0,99 bar - 15 bar                  |
| Temperaturno područje | -20 °C to +80 °C                    |
| Brtva                 | NBR                                 |
| Kućište               | Nickel-plated brass                 |
| Stezni prsten         | Stainless steel 1.4301              |
| Matica                | Nickel-plated brass                 |
| O prsten              | NBR                                 |
| Sigurnosni prsteni    | Technopolymer                       |



## Artikl

| Naziv          | Vanjski Ø<br>cijevi | Priključak | B    | C    | E    | I    | L1   | L2   | L maks. | L min. | M    | N    | O    | P    | SW1  | SW2  |
|----------------|---------------------|------------|------|------|------|------|------|------|---------|--------|------|------|------|------|------|------|
|                |                     |            | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm)    | (mm)   | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| K- 07 40 54 14 | 20 mm               | G 1/2"     | 31,5 | 20,0 | 34,5 | 28,5 | 27,0 | 51,5 | 54      | 22     | 74   | 61   | 30,5 | 5    | 26   | 30   |
| K- 07 40 54 15 | 25 mm               | G 1/2"     | 38,5 | 21,0 | 42,5 | 28,5 | 27,0 | 59,0 | 54      | 22     | 74   | 61   | 30,5 | 5    | 26   | 35   |