

# K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

**HANSA FLEX**

## Karakteristike

maks. radni tlak	0,7 MPa
min. pogonski tlak	0.10 MPa
Izvedba	rack and pinion
Temperatura medija	0 °C to +60 °C
Okolna temperatura	0 °C to +60 °C
Zakretni kut	0 to 190°
Mediji	komprimirani zrak
Serija	MSQ
Drugi podatci	narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table Air connections of 2 pages possible



## Artikli

Naziv	Ø klipa (mm)	Priključak, pneumatski	Veličina	Prigušivanje	Težina po m (kg)
K- 07 55 01 13	6	M 3	1	without, with adjustment bolt	0,075
K- 07 55 01 18	8	M 5	2	without, with adjustment bolt	0,105
K- 07 55 01 21	10	M 5	3	elastic, with adjustment bolt	0,150
K- 07 55 01 26	12	M 5	7	elastic, with adjustment bolt	0,250
K- 07 55 01 11	15	M 5	10	elastic, with adjustment bolt	0,530
K- 07 55 01 16	18	M 5	20	elastic, with adjustment bolt	0,990
K- 07 55 01 19	21	G 1/8	30	elastic, with adjustment bolt	1,290
K- 07 55 01 22	25	G 1/8	50	elastic, with adjustment bolt	2,080
K- 07 55 01 24	28	G 1/8	70	elastic, with adjustment bolt	2,880
K- 07 55 01 09	32	G 1/8	100	elastic, with adjustment bolt	4,090
K- 07 55 01 14	40	G 1/8	200	elastic, with adjustment bolt	7,580
K- 07 55 01 12	15	M 5	10	elastic, with integrated shock absorber	0,540
K- 07 55 01 17	18	M 5	20	elastic, with integrated shock absorber	0,990
K- 07 55 01 20	21	G 1/8	30	elastic, with integrated shock absorber	1,290
K- 07 55 01 23	25	G 1/8	50	elastic, with integrated shock absorber	2,100
K- 07 55 01 25	28	G 1/8	70	elastic, with integrated shock absorber	2,880
K- 07 55 01 10	32	G 1/8	100	elastic, with integrated shock absorber	4,100
K- 07 55 01 15	40	G 1/8	200	elastic, with integrated shock absorber	7,650