

# K-PNEUMA KOMPAKTSCHLITTEN MXS

Air Slide Table MXS

**HANSA FLEX**

## Karakteristike

|                    |  |
|--------------------|--|
| maks. radni tlak   | 0,7 MPa  |
| min. pogonski tlak | 0.15 MPa   |
| Prigušivanje       | elastic stop   |
| Funkcija           | double working   |
| Ispitni tlak       | 1,05 MPa   |
| Temperatura medija | -10 °C to +60 °C   |
| Okolna temperatura | -10 °C to +60 °C   |
| Brzina klipa       | 50 to 500 mm/s   |
| Mediji             | komprimirani zrak  |
| Serijski           | MXS  |
| Drugi podatci      | Carriage and air cylinder as a complete unit<br>Ideal for precision assembly applications<br>High resistance to the cultivation of loads |



## Opis

Compact air slide table, series MXS, slide table and air cylinder as complete unit, ideal for precise installation applications, high resistance capacity when building up loads, with stroke limiting unit or shock absorber, (order separately), no stroke adjustment, double action, piston diameter / stroke: 20/100 mm, connection size: G 1/8

## Artikli

| Naziv          | Ø klipa (mm) | Hod (mm) | Priključak, pneumatski | Težina (kg) |
|----------------|--------------|----------|------------------------|-------------|
| K- 07 55 01 46 | 6            | 10       | M 3                    | 0,080       |
| K- 07 55 01 47 | 6            | 20       | M 3                    | 0,100       |
| K- 07 55 01 48 | 6            | 30       | M 3                    | 0,115       |
| K- 07 55 01 49 | 6            | 40       | M 3                    | 0,155       |
| K- 07 55 01 50 | 6            | 50       | M 3                    | 0,180       |
| K- 07 55 01 52 | 8            | 10       | M 5                    | 0,150       |
| K- 07 55 01 53 | 8            | 20       | M 5                    | 0,160       |
| K- 07 55 01 54 | 8            | 30       | M 5                    | 0,190       |
| K- 07 55 01 55 | 8            | 40       | M 5                    | 0,235       |
| K- 07 55 01 56 | 8            | 50       | M 5                    | 0,285       |
| K- 07 55 01 57 | 8            | 75       | M 5                    | 0,410       |
| K- 07 55 01 27 | 12           | 10       | M 5                    | 0,325       |
| K- 07 55 01 29 | 12           | 20       | M 5                    | 0,325       |
| K- 07 55 01 30 | 12           | 30       | M 5                    | 0,325       |
| K- 07 55 01 31 | 12           | 40       | M 5                    | 0,385       |
| K- 07 55 01 32 | 12           | 50       | M 5                    | 0,485       |
| K- 07 55 01 33 | 12           | 75       | M 5                    | 0,660       |
| K- 07 55 01 28 | 12           | 100      | M 5                    | 0,890       |
| K- 07 55 01 35 | 16           | 10       | M 5                    | 0,570       |
| K- 07 55 01 38 | 16           | 20       | M 5                    | 0,570       |
| K- 07 55 01 39 | 16           | 30       | M 5                    | 0,580       |
| K- 07 55 01 40 | 16           | 40       | M 5                    | 0,640       |
| K- 07 55 01 41 | 16           | 50       | M 5                    | 0,760       |
| K- 07 55 01 42 | 16           | 75       | M 5                    | 1,090       |
| K- 07 55 01 36 | 16           | 100      | M 5                    | 0,770       |
| K- 07 55 01 37 | 16           | 125      | M 5                    | 0,900       |
| K- 07 55 00 01 | 20           | 10       | G 1/8                  | 0,960       |
| K- 07 55 00 05 | 20           | 20       | G 1/8                  | 0,980       |
| K- 07 55 00 06 | 20           | 30       | G 1/8                  | 1,010       |
| K- 07 55 00 07 | 20           | 40       | G 1/8                  | 1,100       |
| K- 07 55 00 08 | 20           | 50       | G 1/8                  | 1,250       |
| K- 07 55 00 09 | 20           | 75       | G 1/8                  | -           |
| K- 07 55 00 02 | 20           | 100      | G 1/8                  | 2,150       |
| K- 07 55 00 03 | 20           | 125      | G 1/8                  | 2,670       |
| K- 07 55 00 04 | 20           | 150      | G 1/8                  | 3,190       |



Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.

02.05.2026

HANSA-FLEX AG

www.hansa-flex.com

1

# K-PNEUMA KOMPAKTSCHLITTEN MXS

Air Slide Table MXS



## Artikl

| Naziv          | Ø klipa<br>(mm) | Hod<br>(mm) | Priključak, pneumatski | Težina<br>(kg) |
|----------------|-----------------|-------------|------------------------|----------------|
| K- 07 55 00 10 | 25              | 10          | G 1/8                  | 1,660          |
| K- 07 55 00 14 | 25              | 20          | G 1/8                  | 1,680          |
| K- 07 55 00 15 | 25              | 30          | G 1/8                  | 1,690          |
| K- 07 55 00 16 | 25              | 40          | G 1/8                  | 1,840          |
| K- 07 55 00 17 | 25              | 50          | G 1/8                  | 2,090          |
| K- 07 55 00 18 | 25              | 75          | G 1/8                  | 2,650          |
| K- 07 55 00 11 | 25              | 100         | G 1/8                  | 3,270          |
| K- 07 55 00 12 | 25              | 125         | G 1/8                  | 4,140          |
| K- 07 55 00 13 | 25              | 150         | G 1/8                  | 4,170          |