

# K-W90 DRV AS-FS

Speed controllers, 90°, connection plug, with built-in indicator

**HANSA FLEX**

## Karakteristike

|                                |   |
|--------------------------------|---|
| <b>maks. radni tlak</b>        | 1 MPa   |
| <b>min. pogonski tlak</b>      | 0.10 MPa  |
| <b>Odvojeci</b>                | 1   |
| <b>Broj dovodnih vodova</b>    | 1   |
| <b>Smjer prikaznog prozora</b> | 0°  |
| <b>Boja okretne glave</b>      | Blue  |
| <b>Ispitni tlak</b>            | 1,50 MPa  |
| <b>Upravljanje</b>             | Flow governing  |
| <b>Temperatura medija</b>      | -5 °C to +60 °C (ohne Gefrieren)  |
| <b>Okolna temperatura</b>      | -5 °C bis +60 °C (no freezing)  |
| <b>Mediji</b>                  | komprimirani zrak   |
| <b>Materijal crijeva</b>       | polyamid, soft polyamid, polyurethane, FEP, PFA   |
| <b>Serijski naziv</b>          | AS-FS   |
| <b>Drugi podatci</b>           | large rotary knob with push-lock latch<br>larger free space under the hose<br>Lockable rotary knob, numeric display |



## Artikli

| Naziv          | Veličina | Priključak odvojka     | Priključak za dovodni vod | Izvedba                   | Okretaji igle | Težina po m (kg) |
|----------------|----------|------------------------|---------------------------|---------------------------|---------------|------------------|
| K- 07 30 30 54 | 1        | for hose outer-Ø2 mm   | outer thread M 5          | with sealing ring         | 8             | 0,007            |
| K- 07 30 30 57 | 1        | for hose outer-Ø3.2 mm | outer thread M 5          | with sealing ring         | 8             | 0,007            |
| K- 07 30 30 55 | 1        | for hose outer-Ø4 mm   | outer thread M 5          | with sealing ring         | 8             | 0,007            |
| K- 07 30 30 56 | 1        | for hose outer-Ø6 mm   | outer thread M 5          | with sealing ring         | 8             | 0,008            |
| K- 07 30 30 62 | 2        | for hose outer-Ø3.2 mm | outer thread R 1/8        | Teflon coated             | 10            | 0,007            |
| K- 07 30 30 67 | 2        | for hose outer-Ø3.2 mm | outer thread R 1/4        | Teflon coated             | 10            | 0,023            |
| K- 07 30 30 58 | 2        | for hose outer-Ø4 mm   | outer thread R 1/8        | Teflon coated             | 10            | 0,013            |
| K- 07 30 30 63 | 2        | for hose outer-Ø4 mm   | outer thread R 1/4        | Teflon coated             | 10            | 0,023            |
| K- 07 30 30 59 | 2        | for hose outer-Ø6 mm   | outer thread R 1/8        | Teflon coated             | 10            | 0,014            |
| K- 07 30 30 68 | 2        | for hose outer-Ø6 mm   | outer thread G 1/8        | surface with sealing ring | 10            | 0,014            |
| K- 07 30 30 64 | 2        | for hose outer-Ø6 mm   | outer thread R 1/4        | Teflon coated             | 10            | 0,023            |
| K- 07 30 30 69 | 2        | for hose outer-Ø6 mm   | outer thread G 1/4        | surface with sealing ring | 10            | 0,023            |
| K- 07 30 30 60 | 2        | for hose outer-Ø8 mm   | outer thread R 1/8        | Teflon coated             | 10            | 0,015            |
| K- 07 30 30 65 | 2        | for hose outer-Ø8 mm   | outer thread R 1/4        | Teflon coated             | 10            | 0,024            |
| K- 07 30 30 70 | 2        | for hose outer-Ø8 mm   | outer thread G 1/4        | surface with sealing ring | 10            | 0,024            |
| K- 07 30 30 61 | 2        | for hose outer-Ø10 mm  | outer thread R 1/8        | Teflon coated             | 10            | 0,016            |
| K- 07 30 30 66 | 2        | for hose outer-Ø10 mm  | outer thread R 1/4        | Teflon coated             | 10            | 0,025            |
| K- 07 30 30 71 | 2        | for hose outer-Ø10 mm  | outer thread G 1/4        | surface with sealing ring | 10            | 0,025            |
| K- 07 30 30 72 | 3        | for hose outer-Ø6 mm   | outer thread R 3/8        | Teflon coated             | 10            | 0,038            |
| K- 07 30 30 76 | 3        | for hose outer-Ø6 mm   | outer thread G 3/8        | surface with sealing ring | 10            | 0,038            |
| K- 07 30 30 73 | 3        | for hose outer-Ø8 mm   | outer thread R 3/8        | Teflon coated             | 10            | 0,038            |
| K- 07 30 30 77 | 3        | for hose outer-Ø8 mm   | outer thread G 3/8        | surface with sealing ring | 10            | 0,038            |
| K- 07 30 30 74 | 3        | for hose outer-Ø10 mm  | outer thread R 3/8        | Teflon coated             | 10            | 0,029            |
| K- 07 30 30 78 | 3        | for hose outer-Ø10 mm  | outer thread G 3/8        | surface with sealing ring | 10            | 0,029            |
| K- 07 30 30 75 | 3        | for hose outer-Ø12 mm  | outer thread R 3/8        | Teflon coated             | 10            | 0,041            |
| K- 07 30 30 79 | 4        | for hose outer-Ø10 mm  | outer thread R 1/2        | Teflon coated             | 10            | 0,062            |
| K- 07 30 30 82 | 4        | for hose outer-Ø10 mm  | outer thread G 1/2        | surface with sealing ring | 10            | 0,062            |
| K- 07 30 30 80 | 4        | for hose outer-Ø12 mm  | outer thread R 1/2        | Teflon coated             | 10            | 0,064            |
| K- 07 30 30 83 | 4        | for hose outer-Ø12 mm  | outer thread G 1/2        | surface with sealing ring | 10            | 0,064            |
| K- 07 30 30 81 | 4        | for hose outer-Ø16 mm  | outer thread R 1/2        | Teflon coated             | 10            | 0,068            |
| K- 07 30 30 84 | 4        | for hose outer-Ø16 mm  | outer thread G 1/2        | surface with sealing ring | 10            | 0,068            |