

K-ROHRLEIT ALU KALIBRIERT GRAU INFI

Pipe made of aluminium, calibrated, grey

HANSA FLEX

Karakteristike

Mediji	Compressed air, vacuum, inert gases
Koeficijent rastezanja	0,024 mm/m °C
Radni tlak	-0,99 bar - 15 bar
Temperaturno područje	-20 °C to +80 °C
Boja	greyRAL 7035
Materijal	Aluminium UNI 9006/1 Al Mg 0,5 Si 0,4 Fe 0,2
Površinska obrada	electrostatic coating



Napomene uz narudžbu

Special lengths on request

Artikli

Naziv	Vanjski Ø (mm)	Debljina stjenki (mm)	Težina po m (kg)	Specifična težina po dm ³ (kg)	Duljina (m)	Jedinica ambalaže
K- 07 40 53 15	20	1,5	0,235	2,7	4,000	1 piece
K- 07 40 53 30	20	1,5	0,235	2,7	6,000	1 piece
K- 07 40 53 16	25	1,5	0,298	2,7	4,000	1 piece
K- 07 40 53 31	25	1,5	0,298	2,7	6,000	1 piece
K- 07 40 53 17	32	1,5	0,387	2,7	4,000	1 piece
K- 07 40 53 32	32	1,5	0,387	2,7	6,000	1 piece
K- 07 40 53 18	40	1,5	0,490	2,7	4,000	1 piece
K- 07 40 53 33	40	1,5	0,490	2,7	6,000	1 piece
K- 07 40 53 19	50	2,0	0,814	2,7	4,000	1 piece
K- 07 40 53 34	50	2,0	0,814	2,7	6,000	1 piece
K- 07 40 53 20	63	2,0	1,034	2,7	4,000	1 piece
K- 07 40 53 35	63	2,0	1,034	2,7	6,000	1 piece
K- 07 40 55 08	80	2,0	1,493	2,7	4,000	1 piece
K- 07 40 55 10	80	2,0	1,493	2,7	6,000	1 piece
K- 07 40 53 21	110	2,5	2,280	2,7	4,000	1 piece
K- 07 40 53 36	110	2,5	2,280	2,7	6,000	1 piece