

K-ROHRLEIT ALU KALIBRIERT GRAU INFI

Pipe made of aluminium, calibrated, grey

HANSA FLEX

Karakteristike

| | |
|------------------------|--|
| Mediji | Compressed air, vacuum, inert gases |
| Koeficijent rastezanja | 0,024 mm/m °C |
| Radni tlak | -0,99 bar - 15 bar |
| Temperaturno područje | -20 °C to +80 °C |
| Boja | greyRAL 7035 |
| Materijal | Aluminium UNI 9006/1 Al Mg 0,5 Si 0,4 Fe 0,2 |
| Površinska obrada | electrostatic coating |



Napomene uz narudžbu

Special lengths on request

Artikli

| Naziv | Vanjski Ø (mm) | Debljina stjenki (mm) | Težina po m (kg) | Specifična težina po dm ³ (kg) | Duljina (m) | Jedinica ambalaže |
|----------------|-------------------|--------------------------|---------------------|--|----------------|-------------------|
| K- 07 40 53 15 | 20 | 1,5 | 0,235 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 30 | 20 | 1,5 | 0,235 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 16 | 25 | 1,5 | 0,298 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 31 | 25 | 1,5 | 0,298 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 17 | 32 | 1,5 | 0,387 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 32 | 32 | 1,5 | 0,387 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 18 | 40 | 1,5 | 0,490 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 33 | 40 | 1,5 | 0,490 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 19 | 50 | 2,0 | 0,814 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 34 | 50 | 2,0 | 0,814 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 20 | 63 | 2,0 | 1,034 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 35 | 63 | 2,0 | 1,034 | 2,7 | 6,000 | 1 piece |
| K- 07 40 55 08 | 80 | 2,0 | 1,493 | 2,7 | 4,000 | 1 piece |
| K- 07 40 55 10 | 80 | 2,0 | 1,493 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 21 | 110 | 2,5 | 2,280 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 36 | 110 | 2,5 | 2,280 | 2,7 | 6,000 | 1 piece |