

# LKM HR ST DK

Kolčak utične spojke (zrak) s osiguračem

**HANSA FLEX**

## Karakteristike

Izvedba	Brzo zaporni spojni kolčak
Priključak 1	BSP vanjski navoj, cilindrični
Priključak 2	
Radni tlak	maks. 12 bara
Protok zraka	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatura medija	-20 °C to +70 °C
Kućište	Aluminium, anodised
Navoj	Nickel-plated brass
Unutarnji dijelovi	Stainless steel
Gumb, ventil	Hardened, galvanised steel
Brtveni materijal	NBR



## Napomena

Not suitable for hitting / pulsating tools.

Drugi podatci na zahtjev.

## Opis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Artikli

Naziv	Navoj priključka	Priključak	Duljina (mm)	SW (mm)
LKM 06 HR ST DK	G 1/4" -19	G 1/4 male	70,5	21
LKM 10 HR ST DK	G 3/8" -19	G 3/8 male	70,0	21
LKM 13 HR ST DK	G 1/2" -14	G 1/2 male	72,5	25