


K-MANO ABSPH ZAPF DREH MUF2

Pressure gauge stopcocks, male - loose (rotatable) female

Tulajdonságok

Alkalmazás	For all pressure gauges with a flat gasket acc. to DIN 16258
Nyomástartomány	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
Hőmérséklet	Max. +50 °C
ház	Brass with a bare metal surface or stainless steel 1.4571
Fogantyú	Plastic
Vizsgálókarima	-



Megjegyzés

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
További adatokért vegye fel a kapcsolatot.

Leírás

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

További információk

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Cikk

Megnevezés	Menet	PN (bar)	SW (mm)	Anyag
K- 07 20 11 17	G 1/2	25	27	Sárgaréz
K- 07 20 11 18	G 1/2	25	27	Sárgaréz