

K-SPIR SCHL

Spiral hose, without fittings

Tulajdonságok

Alkalmazás	Air, gases, oils, greases, fuels, organic and inorganic substances
Üzemi hőmérséklet	-40 °C to +100 °C



Megjegyzés

További adatokért vegye fel a kapcsolatot.

Leírás

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Cikk

Megnevezés	Ø tömlő belül (mm)	Ø tömlő kívül (mm)	Ø spirál kívül (mm)	Tekerés	Max. working pressure resistance at 23°C (bar)	max. munkahossz (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

Tartozék

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector