

# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

**HANSA FLEX**

## Tulajdonságok

Csatlakozási mód with kink protector, swivel type

Üzemi hőmérséklet -40 °C to +74 °C



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Cikk

Megnevezés	Menet	Ø tömlő belül (mm)	Ø tömlő kívül (mm)	Ø Külső tekerces (mm)	Max. working pressure resistance at 23°C (bar)	max. munkahossz (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

## Tartozék

K-DREHBARE VERSCHRAUBUNG Swivel adapters