


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Tulajdonságok

Üzemi nyomás	0 - 35 bar, maximum static working pressure (non-pulsating)
Levegő átláramlás	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Közeghőmérséklet	-20 °C to +100 °C
Oldóhüvely	Anodised aluminium
Rugók, biztosítógyűrű, golyók	stain less steel
Tömítő anyag	NBR



Megjegyzés

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. További adatokért vegye fel a kapcsolatot.

Leírás

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Cikk

Megnevezés	Csatlakozás	Szín	Hossz (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zöld	45,0	14
K- 07 35 06 81	G 1/4 male	zöld	47,0	17
K- 07 35 06 82	G 1/8 female	zöld	45,0	14
K- 07 35 06 83	G 1/4 female	zöld	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	kék	45,0	14
K- 07 35 06 89	G 1/4 male	kék	47,0	17
K- 07 35 06 90	G 1/8 female	kék	45,0	14
K- 07 35 06 91	G 1/4 female	kék	47,0	17
K- 07 35 06 92	G 1/8 male	piros	45,0	14
K- 07 35 06 93	G 1/4 male	piros	47,0	17
K- 07 35 06 94	G 1/8 female	piros	45,0	14
K- 07 35 06 95	G 1/4 female	piros	47,0	17