


K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Tulajdonságok

Üzemi nyomás	0 - 35 bar, maximum static working pressure (non-pulsating)
Levegő átlámlás	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Közeghőmérséklet	-20 °C to +100 °C
ház	Brass
Szelep	Die-cast zinc, nickel-plated
Oldóhüvely	Anodised aluminium
Rugók, biztosítógyűrű, golyók	stain less steel
Tömítő anyag	NBR



Megjegyzés

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. További adatokért vegye fel a kapcsolatot.

Leírás

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Cikk

Megnevezés	Csatlakozás	Szín	Hossz (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	zöld	57,5	19
K- 07 35 08 02	G 3/8 male	zöld	57,5	19
K- 07 35 08 03	G 1/4 female	zöld	55,5	19
K- 07 35 08 04	G 3/8 female	zöld	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	kék	57,5	19
K- 07 35 08 10	G 3/8 male	kék	57,5	19
K- 07 35 08 11	G 1/4 female	kék	55,5	19
K- 07 35 08 12	G 3/8 female	kék	54,5	19
K- 07 35 08 13	G 1/4 male	piros	57,5	19
K- 07 35 08 14	G 3/8 male	piros	57,5	19
K- 07 35 08 15	G 1/4 female	piros	55,5	19
K- 07 35 08 16	G 3/8 female	piros	54,5	19