K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

Tulajdonságok

Közeghőmérséklet	-5 °C to +80 °C
max. kikapcsolási nyomás	16 bar
Kapcsolási képesség	5,5 kW
Érintkező fajta	NC (3-pole)
max. kapcsolási frekvencia	120 (electrical), 600 (mechanical)
Védettség	IP 54



Megjegyzés

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
További adatokért vegye fel a kapcsolatot.

Leírás

Three-phase version

Rendelési útmutató

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

További információk

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Cikk

Megnevezés	Sűrített levegő csatlakozó	Beállítási tartomány
K- 07 30 24 25	G 1/2	2,0 - 11,0 bar
K- 07 30 24 27	G 1/2	2,5 - 16,0 bar