

# K-WTEH 2-TLG MET SICH TROPF MULTIFI

Service units, 2-piece with metal bowl and sight glass, metal sight dome

**HANSA FLEX**

## Tulajdonságok

|                                  |  |
|----------------------------------|--|
| <b>Bemeneti nyomás</b>           | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)     |
| <b>Közeghőmérséklet</b>          | max. 60 °C   |
| <b>Környezeti hőmérséklet</b>    | Max. 60 °C   |
| <b>Pórusméret a szűrőelemben</b> | 5 µm (BG 1 / BG 2), 40 µm (BG 3)                               |
| <b>Tömítő anyag</b>              | NBR  |
| <b>Rugóburkolat</b>              | POM-brass  |
| <b>ház</b>                       | Die-cast zinc, Aluminium for G 1 variant                       |
| <b>Cseppfeltét</b>               | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)           |
| <b>Drain valve</b>               | Semi-automatic   |
| <b>Átáramlási érték mérés</b>    | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Rendelési útmutató

2-piece service units are also available in other control ranges (0.1 - 3 bar, 0.2 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

## További információk

1500 l/min: P1: 10 bar, P2: 7 bar,  $\Delta p \leq 0.1$  bar.

## Cikk

| Megnevezés     | Menet | Szabályozási tartomány | Átfolyt mennyiség, tömegáram (L/min) | A (mm) | B        | C (mm) | D (mm) | DN | Méret |
|----------------|-------|------------------------|--------------------------------------|--------|----------|--------|--------|----|-------|
| K- 07 25 01 30 | G 1/4 | 0.5 - 10 bar           | 1100                                 | 93,0   | 196,0 mm | 67,0   | 129,0  | 6  | 1     |
| K- 07 25 01 33 | G 3/8 | 0.5 - 10 bar           | 1100                                 | 93,0   | 196,0 mm | 67,0   | 129,0  | 10 | 1     |
| K- 07 25 01 36 | G 1/2 | 0.5 - 10 bar           | 3500                                 | 136,0  | 248,0 mm | 97,0   | 151,0  | 15 | 2     |
| K- 07 25 01 39 | G 3/4 | 0.5 - 10 bar           | 3500                                 | 136,0  | 248,0 mm | 97,0   | 151,0  | 20 | 2     |
| K- 07 25 01 42 | G 1   | 0.5 - 10 bar           | 10500                                | 200,0  | 385,0 mm | 128,0  | 257,0  | 25 | 3     |

## Pótalkatrészek

|                                  |                               |
|----------------------------------|-------------------------------|
| K-HALTERBAUSATZ MULTIFIX         | Holder                        |
| K-KOPPELPAKET MEHR               | Coupling packet               |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler              |
| K-PC-BEHAELTER FILTER MULTIFIX   | Polycarbonate tank filter     |
| K-SCHUTZKORB G                   | Protective cage               |
| K-TROPFAUFSATZ POLYCARBO 1       | Drip attachment polycarbonate |
| K-TROPFAUFSATZ METALL            | Drip attachment metal         |
| K-FILTERELEMENT                  | Filter element                |
| K-AUTOMAT ABLASSVENTIL           | Automatic drain valve         |
| K-VERSCHLEI-SATZ                 | Set of wearing parts          |
| K-HALTERBAUSATZ                  | Holder                        |
| K-SCHALTTAFELMUTTER              | Nut                           |
| K-KOPPELPAKET SCHMA              | Coupling packet               |