

# K-WTEH 3-TLG MET TROPF MULTIFIX-MIN

Service units, 3-piece with metal bowl and metal sight dome

**HANSA FLEX**

## Tulajdonságok

|                                  |   |
|----------------------------------|---|
| <b>Bemeneti nyomás</b>           | Max. 12 bar (also for metal tank!)                                |
| <b>Közeghőmérséklet</b>          | max. 60 °C  |
| <b>Környezeti hőmérséklet</b>    | Max. 60 °C  |
| <b>Pórusméret a szűrőelemben</b> | 5 µm  |
| <b>Tömítő anyag</b>              | NBR   |
| <b>Rugóburkolat</b>              | POM-brass   |
| <b>ház</b>                       | Die-cast zinc   |
| <b>Cseppfeltét</b>               | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)              |
| <b>Drain valve</b>               | Semi-automatic  |
| <b>Átáramlási érték mérés</b>    | At P1 = 8 bar, P2 = 6 bar and pressure drop<br>$\Delta p = 1$ bar |



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

Two or three-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Rendelési útmutató

Lockable service units available on request. If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.

## Cikk

| Megnevezés     | Menet | Szabályozási tartomány | Átfolyt mennyiség, tömegáram<br>(L/min) | A<br>(mm) | B        | C<br>(mm) | D<br>(mm) | DN | Méret |
|----------------|-------|------------------------|---|-----------|----------|-----------|-----------|----|-------|
| K- 07 25 01 07 | G 1/8 | 0.5 - 10 bar           | 700                                     | 120,0     | 162,3 mm | 63,0      | 99,3      | 5  | 0     |
| K- 07 25 01 09 | G 1/4 | 0.5 - 10 bar           | 700                                     | 120,0     | 162,3 mm | 63,0      | 99,3      | 5  | 0     |

## Pótalkatrészek

|                                |  |
|--------------------------------|--|
| K-HALTERBAUSATZ                | Holder                                       |
| K-AUTOMAT ABLASSVENTIL         | Automatic drain valve                        |
| K-SCHALTTAFELMUTTER            | Nut  |
| K-KOPPELPAKET MEHR             | Coupling packet                              |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter                    |
| K-ERSATZBEHAELTER MULTI MINI   | Spare tank »multifix-mini« & »standard-mini« |
| K-VERSCHLEI-SATZ               | Set of wearing parts                         |
| K-FILTERELEMENT                | Filter element                               |
| K-TROPFAUFSATZ POLYCARBO 1     | Drip attachment polycarbonate                |
| K-TROPFAUFSATZ METALL          | Drip attachment metal                        |