

# K-FI MIKRO M DIFFERENZ MANO

Micro-filters with differential pressure gauge

**HANSA FLEX**

## Tulajdonságok

|   |   |
|---|---|
| <b>Bemeneti nyomás</b>                                | Min. 4 bar, Max. 16 bar                           |
| <b>Nyomáskülönbség-nyomásmérő kijelzési tartomány</b> | 0 - 2 bar   |
| <b>Ház, szűrőtartály</b>                              | Aluminium   |
| <b>Környezeti hőmérséklet</b>                         | +5 °C to +60 °C                                   |
| <b>Szűrő finomsága</b>                                | 0,01 µm   |
| <b>Hatásfok</b>                                       | 99.9999 %   |
| <b>Szűrőbetét</b>                                     | Borosilicate (with glass-fibre and foam plastic)  |
| <b>Átáramlási érték mérés</b>                         | At P1 = 6 bar and pressure drop $\Delta p$ = 1.5% |



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

## Cikk

| Megnevezés     | Menet   | Átfolyt mennyiség, tömegáram (L/min) | A (mm) | B1 (mm) | B2 (mm) | C (mm) | D (mm) |
|----------------|---------|--------------------------------------|--------|---------|---------|--------|--------|
| K- 07 25 13 02 | G 1/4   | 1300                                 | 82,5   | 407,0   | 335,0   | 57,0   | 353,0  |
| K- 07 25 13 03 | G 3/8   | 1300                                 | 82,5   | 407,0   | 335,0   | 57,0   | 353,0  |
| K- 07 25 13 04 | G 1/2   | 1300                                 | 82,5   | 407,0   | 335,0   | 57,0   | 353,0  |
| K- 07 25 13 05 | G 3/4   | 2000                                 | 82,5   | 477,0   | 405,0   | 57,0   | 493,0  |
| K- 07 25 13 06 | G 1     | 4080                                 | 118,0  | 492,0   | 420,0   | 72,0   | 458,0  |
| K- 07 25 13 07 | G 1 1/4 | 4580                                 | 118,0  | 592,0   | 520,0   | 72,0   | 658,0  |
| K- 07 25 13 08 | G 1 1/2 | 6500                                 | 118,0  | 692,0   | 620,0   | 72,0   | 858,0  |
| K- 07 25 13 09 | G 2     | 9000                                 | 118,0  | 882,0   | 810,0   | 72,0   | 1238,0 |

## Pótalkatrészek

|                                  |                             |
|----------------------------------|-----------------------------|
| <b>K-FILTERELEMEN SONDER</b>     | Filter element              |
| <b>K-VERBINDUNGELEMENTE SOND</b> | Connecting sets             |
| <b>K-HALTERBAUSATZ</b>           | Holder                      |
| <b>K-DIFFERENZDRUCKMANOMETER</b> | Differential pressure gauge |
| <b>K-AUTOMAT ABLASSVENTIL</b>    | Automatic drain valve       |