


# K-FI MIKRO M DIFFERENZ MANO

Micro-filters with differential pressure gauge

**HANSA FLEX**

## Tulajdonságok

<b>Bemeneti nyomás</b>	Min. 4 bar, Max. 16 bar
<b>Nyomáskülönbség-nyomásmérő kijelzési tartomány</b>	0 - 2 bar
<b>Ház, szűrőtartály</b>	Aluminium
<b>Környezeti hőmérséklet</b>	+5 °C to +60 °C
<b>Szűrő finomsága</b>	0,01 µm
<b>Hatásfok</b>	99.9999 %
<b>Szűrőbetét</b>	Borosilicate (with glass-fibre and foam plastic)
<b>Átáramlási érték mérés</b>	At P1 = 6 bar and pressure drop $\Delta p$ = 1.5%



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

## Cikk

Megnevezés	Menet	Átfolyt mennyiség, tömegáram (L/min)	A (mm)	B1 (mm)	B2 (mm)	C (mm)	D (mm)
K- 07 25 13 02	G 1/4	1300	82,5	407,0	335,0	57,0	353,0
K- 07 25 13 03	G 3/8	1300	82,5	407,0	335,0	57,0	353,0
K- 07 25 13 04	G 1/2	1300	82,5	407,0	335,0	57,0	353,0
K- 07 25 13 05	G 3/4	2000	82,5	477,0	405,0	57,0	493,0
K- 07 25 13 06	G 1	4080	118,0	492,0	420,0	72,0	458,0
K- 07 25 13 07	G 1 1/4	4580	118,0	592,0	520,0	72,0	658,0
K- 07 25 13 08	G 1 1/2	6500	118,0	692,0	620,0	72,0	858,0
K- 07 25 13 09	G 2	9000	118,0	882,0	810,0	72,0	1238,0

## Pótalkatrészek

<b>K-FILTERELEMEN SONDER</b>	Filter element
<b>K-VERBINDUNGEELEMENTE SOND</b>	Connecting sets
<b>K-HALTERBAUSATZ</b>	Holder
<b>K-DIFFERENZDRUCKMANOMETER</b>	Differential pressure gauge
<b>K-AUTOMAT ABLASSVENTIL</b>	Automatic drain valve