

K-VORFILTER O MANO

Pre-filters without differential pressure gauge

Tulajdonságok

Bemeneti nyomás	Min. 4 bar, Max. 16 bar
Nyomáskülönbség-nyomásmérő kijelzési tartomány	0 - 2 bar
Ház, szűrőtartály	Aluminium
Környezeti hőmérséklet	+5 °C to +60 °C
Szűrő finomsága	2,00 µm
Részecskeleválasztás	2 µm
Hatásfok	99.99 %
Szűrőbetét	Polyethylene (with 45% cavity)
Átáramlási érték mérés	At P1 = 6 bar and pressure drop Δp = 0.5%



Megjegyzés

További adatokért vegye fel a kapcsolatot.

Leírás

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

Cikk

Megnevezés	Menet	Átfolyt mennyiség, tömegáram (L/min)	A (mm)	B2 (mm)	C (mm)	D (mm)
K- 07 25 12 94	G 1/4	1000	82,5	338,0	57,0	353,0
K- 07 25 12 95	G 3/8	1000	82,5	338,0	57,0	353,0
K- 07 25 12 96	G 1/2	1000	82,5	338,0	57,0	353,0
K- 07 25 12 97	G 3/4	2000	82,5	408,0	57,0	493,0
K- 07 25 12 98	G 1	3000	118,0	423,0	72,0	458,0
K- 07 25 12 99	G 1 1/4	5300	118,0	523,0	72,0	658,0
K- 07 25 13 00	G 1 1/2	8300	118,0	623,0	72,0	858,0
K- 07 25 13 01	G 2	13000	118,0	813,0	72,0	1238,0

Pótalkatrészek

K-FILTERELEMENT SONDER	Filter element
K-VERBINDUNGSELEMENTE SOND	Connecting sets
K-HALTERBAUSATZ	Holder
K-AUTOMAT ABLASSVENTIL	Automatic drain valve