

# K-LP ALU O DUESE

Blow guns die-cast aluminium nickel-plated, without nozzle, Safety

**HANSA FLEX**

## Tulajdonságok

Üzemi nyomás	max. 10 bar
Üzemi hőmérséklet	-10 °C to +50 °C
Fúvókák és toldások	Thread M12x1.25



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

Standard type without nozzle! In combination with the safety nozzles described below, this blow gun meets a wide range of safety requirements. For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

## Cikk

Megnevezés	Csatlakozás	Csatlakozó menet
K- 07 10 00 07	Stem, I.D. 6	G 1/4
K- 07 10 00 10	Stem, I.D. 9	G 1/4
K- 07 10 00 14	Stem, I.D. 13	G 1/4
K- 07 10 00 18	connection nipples for coupling NW 7,2	G 1/4

## Tartozék

K-ZUBEH LP ALU	Accessories for standard blow guns (series 22)
K-FEINSTRAHLDUE LAERMARME M	Low-noise fine-spray nozzles, M12x1.25 connection
K-RUNDDUESE LAERMARME M	Low-noise round nozzles, M12x1.25 connection
K-FLACHDUESE LAERMARME M	Low-noise flat nozzles, M12x1.25 connection
K-STANDARDUESE	Standard nozzle (short version) with Ø 1.5 mm bore
K-DAEMPFERDUESE	Silencer nozzle, M12x1.25 connection
K-DUESE MIT SCHUTZSCHILD	Nozzle with chip shield, M12x1.25 connection
K-VERL DUESE	Extension nozzles
K-DRUCKREGULIERDUESE	Regulating nozzle, M12x1,25, Safety