

K-DRV ABLD GEW C SCHLITZ

Unidirectional flow control valves, outgoing air restriction (»C«), screw connection

HANSA FLEX

Tulajdonságok

| | |
|--|------------------------------------|
| Üzemi nyomás | max. 10 bar |
| Hőmérséklettartomány | 0 °C to +70 °C |
| Üreges csavar, forgatókar, szabályozó csavar | Nickel-plated brass |
| Belső alkatrészek | Brass with a bare metal surface |
| Ajacos tömítés O-gyűrű | NBR |
| Tömítések (nem leeső) | Polyamide (glass fibre-reinforced) |



Megjegyzés

További adatokért vegye fel a kapcsolatot.

Leírás

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.

Cikk

| Megnevezés | Csatlakozás | C (mm) | Menet | SW (Kulcsnyílás) | B (mm) |
|----------------|---------------------|-----------|-------|------------------|-----------|
| K- 07 15 05 40 | M 5 female thread | 11,5 | M 5 | 8 mm | 24,5 |
| K- 07 15 05 45 | G 1/8 female thread | 16,0 | G 1/8 | 14 mm | 32,0 |
| K- 07 15 05 41 | G 1/4 female thread | 22,0 | G 1/4 | 17 mm | 40,0 |
| K- 07 15 25 24 | G 3/8 female thread | 26,0 | G 3/8 | 20 mm | 50,0 |
| K- 07 15 25 23 | G 1/2 female thread | 32,0 | G 1/2 | 26 mm | 61,0 |