# K-DMUF ALLGEMEIN

Pressure transmitters for universal industrial applications, nonlinearity 0.25%

## Tulajdonságok

| | |
|---|---|
| **Típus** | S-20 |
| **Feszültség** | DC 8 ... 36 V |
| **Elektromos csatlakozás** | With right-angle connector acc. to DIN EN 175301-803 A |
| **Védettség** | IP 65 acc. to EN 60529 |
| **Kimeneti jel** | 4 to 20 mA, 2-wire |
| **Nemlinearitás** | up to 0.25% of span |
| **Közeghőmérséklet** | -30 °C to +100 °C |
| **Környezeti hőmérséklet** | -40 °C to +70 °C |
| **Mért anyagot érintő alkatrészek** | CrNi steel 1.4571 |
| **ház** | CrNi steel 1.4571 |



## Leírás

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development. Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry. Compatible with all internationally established process connections.

## További információk

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

## Cikk

| Megnevezés | mérési tartomány | Menet |
|---|---|---|
| **K- 07 20 12 55** | -1 / 0.0 bar | G 1/2 |
| **K- 07 20 12 56** | 0 - 0.4 bar | G 1/2 |
| **K- 07 20 12 57** | 0 - 1.0 bar | G 1/2 |
| **K- 07 20 12 64** | 0 - 4.0 bar | G 1/2 |
| **K- 07 20 12 67** | 0 - 6.0 bar | G 1/2 |
| **K- 07 20 12 58** | 0 - 10.0 bar | G 1/2 |
| **K- 07 20 12 60** | 0 - 16.0 bar | G 1/2 |
| **K- 07 20 12 62** | 0 - 25.0 bar | G 1/2 |
| **K- 07 20 12 65** | 0 - 40.0 bar | G 1/2 |
| **K- 07 20 12 68** | 0 - 60.0 bar | G 1/2 |
| **K- 07 20 12 59** | 0 - 100.0 bar | G 1/2 |
| **K- 07 20 12 61** | 0 - 160.0 bar | G 1/2 |
| **K- 07 20 12 63** | 0 - 250.0 bar | G 1/2 |
| **K- 07 20 12 66** | 0 - 400.0 bar | G 1/2 |
| **K- 07 20 12 69** | 0 - 600.0 bar | G 1/2 |

*Az alapos ellenőrzések ellenére nem tudunk minden hibát kizárni és ezért nem vállalunk felelősséget a megadott adatokért.*