

K-SCHLAUCH KUPPLUNG SET SICH

Hose and coupling kits, with straight hose and DN 7.6 safety coupling

HANSA FLEX

Tulajdonságok

Üzemi nyomás 16 bar

Közeghőmérséklet -20 °C to +60 °C



Megjegyzés

További adatokért vegye fel a kapcsolatot.

Leírás

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

Cikk

| Megnevezés | Tömlőméret | Munkahossz (m) |
|----------------|---------------|-------------------|
| K- 07 10 05 58 | 12 mm x 8 mm | 10,0 |
| K- 07 10 05 59 | 12 mm x 8 mm | 15,0 |
| K- 07 10 05 60 | 16 mm x 11 mm | 10,0 |
| K- 07 10 05 61 | 16 mm x 11 mm | 15,0 |