

# K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

**HANSA FLEX**

## Tulajdonságok

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Közegek                           | Filtered, unlubricated compressed air |
| Üzemi nyomás                      | 2.5 - 8 bar                           |
| Hőmérséklettartomány              | -10 °C to +60 °C                      |
| Csatlakozás                       | Push-in fitting for pipe 4 mm         |
| Működtetés                        | Pneumatic                             |
| Átáramlási mennyiség levegő 6 bar | 85 NI/min                             |
| max. időeltolás bemeneti jel      | 0,4 s                                 |



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

## Cikk

| Megnevezés     | Meghatározás                          | Csatlakozás                   |
|----------------|---------------------------------------|-------------------------------|
| K- 07 15 26 09 | Two-hand safety valve without housing | Push-in fitting for 4 mm pipe |
| K- 07 15 26 10 | mounting element                      | -                             |