

# K-LKM S NW7,8 AG

Safety couplings DN 7.8, male

**HANSA FLEX**

## Tulajdonságok

Üzemi nyomás	max. 20 bar
Levegő átáramlás	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Közeghőmérséklet	-20 °C to +100 °C
Szeleptest csatlakozó	Nickel-plated brass
Rugók, golyók	Stainless-steel
Tolóhüvely	Anodised aluminium
Oldóhüvely	Hardened and nickel-plated steel
Tömítő anyag	NBR



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

## Cikk

Megnevezés	Csatlakozás	Hossz (mm)	SW (mm)
K- 07 35 08 82	R 1/4 male	80,0	19
K- 07 35 08 83	R 3/8 male	81,0	19
K- 07 35 08 84	R 1/2 male	87,0	22

## kiegészítő elemek

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass