

K-SVKM NW 7,6 IG ST

Quick disconnect couplings DN 7.6, galvanised steel / nickel-plated brass, female

HANSA FLEX

Tulajdonságok

Üzemi nyomás	Max. 16 bar
Levegő átláramlás	2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Közeghőmérséklet	-20 °C to +100 °C
ház	Steel
Rugó	Stainless-steel
Tolóhüvely	Hardened and nickel-plated steel
Tömítő anyag	NBR



Megjegyzés

További adatokért vegye fel a kapcsolatot.

Leírás

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The "stream line" type has an integrated hose stem.

Cikk

Megnevezés	Csatlakozás	Hossz (mm)	SW (mm)
K- 07 35 07 80	G 1/4 female	57,0	20
K- 07 35 07 81	G 3/8 female	60,0	22
K- 07 35 07 82	G 1/2 female	60,0	25

Kiegészítő elemek

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel